

CMC-DIGI-AHD Digital Remote for Hoist Controller

The CMC-DIGI-AHD series controller allows controlling of the AHD-LV and AHD-DV series devices via cable connection.

There is a 5-pin Neutrik connector installed on the device for the connection of a cable.

The device comes in 1-, 4-, 6-, 8-, 16- and 24-channel versions.

Power supply

Powered by 5-pin connector

Operating temperature

-20 °C to +40 °C

Housing

3mm lightweight aluminum box

Dimensions & Weight

CMC48-DIGI-AHD: 107x330x105 mm, 5kg

CMC24-DIGI-AHD: 107x260x105 mm, 4kg

CMC12-DIGI-AHD: 107x360x105 mm, 2kg

CMC8-DIGI-AHD: 107x260x105 mm, 2kg

CMC6-DIGI-AHD: 107x260x105 mm, 2kg

CMC4-DIGI-AHD: 107x190x105 mm, 2kg

Warranty

2 years



- Cable remote DIGITAL controller for AHDseries
- Controls up to 60 channels
- High-quality switches with covers against dust and water
- LED signalization of POWER/STATUS
- LED signalization of GO button and Direction positions
- 5-pin Neutrik connector

Pin	Function	note
1	Data CMN	<i>Data Common</i>
2	Data -	<i>Data Minus</i>
3	Data+	<i>Data Plus</i>
4	DC1	<i>Power supply for CMC DC12-36V</i>
5	DC2	<i>Power supply for CMC DC12-36V</i>

CMC-DIGI-AHD_datasheet_M317

