

DMX2SW

2-channel

DMX Switch

The DMX2SW device allows controlling of 2x 230V/50Hz 8A electrical devices from theatrical light desk via the DMX line.

Switching of the output is done via the relays for phase and neutral lines. The DMX2SW device is equipped with a socket according to customer's needs.

Custom made firmware is available upon request.



Power supply

AC 230V / 50Hz, 16A

Operating temperature

-20 °C to +60 °C

Housing

Steel housing with powder coating

Dimensions & Weight

110 x 44 x 145mm, 1.0kg

Warranty

2 years



DMX2SW features:

- 2-channel Phase and Neutral switch
- Relay protection for 100A spike
- Over-voltage protection of the DMX input
- LED indication of the DMX line
- DIP switch for the DMX address setting
- Neutrik 3 or 5-pin on request

Outputs:

- Schuko
- French Schuko
- Swiss
- CEE16/3p
- Danish

DMX input with true output:

USITT DMX 512 (1990)


Switching output:

- 1x 230V / 16A
- fused with 16A fuse and optical signalization of active output channel on the top panel by a glow lamp


DMX2SW_en_datasheet_M041

XLR 3- or 5- pin connector (Neutrik®):

Pin 1	Data CMN
Pin 2	Data -
Pin 3	Data +
Pin 4, 5	not connected



Front panel description



1. DMX input connector
2. DMX output connector
3. DMX start address selector
4. DMX and power status LEDs